

KAESER
KOMPRESSOREN®



Program MOBILAIR S CE usklađenošću

Mobilni kompresori sa svjetski priznatim sustavom SIGMA PROFIL ⚙️

Količina dobave od 1,2 do 48,1 m³/min

www.kaeser.com

Alternativni pogoni

			e-power			
Model			M 13	M 17	M 10E	M 13E
Volumni protok pri maks. radnom pretlaku	7 bara	m³/min	1,2	–	0,85	1,25
	100 psi	cfm	42		30	44
	10 bara	m³/min	1	–	0,75	1
	145 psi	cfm	35		27	35
	13 bara	m³/min	0,85	–	0,65	0,85
	190 psi	cfm	30		22	30
	15 bara	m³/min	–	1	0,55	0,75
	215 psi	cfm		35	19	27
Tip motora			Honda GX 630	Honda GX 630	Innomotics	Innomotics
Nazivna snaga motora (kW)			15,5	15,5	5,5	7,5
Obrada komprimiranog zraka			Opcija	Opcija	Opcija	Opcija



Kompaktni uređaji

			e-power					
Model			M 20	M 27	M 30	M 27E	M 31E	M 50E
Volumni protok pri maks. radnom pretlaku	7 bara	m³/min	2	2,6	2,9	2,6	3,15	5
	100 psi	cfm	71	92	100	92	110	180
	10 bara	m³/min	–	2,1	–	–	2,6	3,8
	145 psi	cfm		74			92	135
	12 bara	m³/min	–	1,9	–	–	2,3	–
	175 psi	cfm		67			81	
	14 bara	m³/min	–	1,6	–	–	1,9	–
	200 psi	cfm		57			67	
Tip motora			Kubota D722	Kubota D1105	Kubota D1105T	Innomotics	Innomotics	Innomotics
Nazivna snaga motora (kW)			14,7	18,2	18,2	15	22	25
Obrada komprimiranog zraka			Opcija	Opcija	Opcija	Opcija	Opcija	Opcija
Generator (kVA)			–	6,5	–	–	–	–




Višenamjenski uređaji

Model			M 44	M 58 utility	M 59	M 65
Volumni protok pri maks. radnom pretlaku	7 bara	m³/min	4,1	5,1	–	–
	100 psi	cfm	145	180		
	10 bara	m³/min	–	4,35	4,7 pV 5,5	5,8 pV 6,6
	145 psi	cfm		155	165 195	195 230
	14 bara	m³/min	–	–	3,8 pV 4,7	4,6 pV 5,8
	200 psi	cfm			135 165	165 195
Tip motora			Kubota V1505CR-T	Kubota V2403CR	Hatz 3H50TICD	Kubota V2403CR-T
Nazivna snaga motora (kW)			27,5	35,5	43,5	47,9
Obrada komprimiranog zraka			Opcija	Opcija	Opcija	Opcija
Generator (kVA)			8,5 / 13	–	8,5 / 13	–



Snažni uredaji

Model			M 76		M 81		M 125		M 171		
Volumni protok pri maks. radnom pretlaku	7 bara	m³/min	-		-		-		17		
	100 psi	cfm							600		
	10 bara	m³/min	6,8	pV	7,7	7,1	pV	8,3	-		
	145 psi	cfm	240		270	250		295	-		
	14 bara	m³/min	5,3	pV	6,1	5,3	pV	6,4	11,5	pV	11,5
	200 psi	cfm	190		215	190		230	405		550
Tip motora			Kubota V3307CR-T		Hatz 4H50TICD		Deutz TCD 4.1 L04		Deutz TCD 6.1 L06		
Nazivna snaga motora (kW)			55,4		55,4		105		129		
Obrada komprimiranog zraka			Opcija		Opcija		Opcija		Opcija		
Generator (kVA)			-		8,5 / 13		13		-		



Veliki kompresori

Model				M 255		e-power	
						M 250E	M 255E
Volumni protok pri maks. radnom pretlaku	8,6 bara	m³/min	-		25		-
	125 psi	cfm			885		
	10,3 bara	m³/min	24,8	pV	26,5	20,4	24,7
	150 psi	cfm	875		950	720	875
	12 bara	m³/min	-		-		19,9
	175 psi	cfm					705
	14 bara	m³/min	19,7	pV	25,5	16,2	-
	200 spi	cfm	695		900	570	
Tip motora			Cummins B6.7		Innomotics	Innomotics	
Nazivna snaga motora (kW)			210		132	160	
Obrada komprimiranog zraka			Opcija		Opcija	Opcija	

