

**KAESER**  
KOMPRESORJI®



# Program MOBILAIR s skladnostjo CE

Mobilni kompresorji s svetovno priznanim SIGMA PROFILOM ⚙️

Dobavna količina od 1,2 do 48,1 m³/min

[www.kaeser.com](http://www.kaeser.com)

Alternativni pogoni

|                                                   |          |        | e-power      |              |            |            |
|---------------------------------------------------|----------|--------|--------------|--------------|------------|------------|
| Model                                             |          |        | M 13         | M 17         | M 10E      | M 13E      |
| Prostorninski tok pri najv. obratovalnem nadtlaku | 7 barov  | m³/min | 1,2          | –            | 0,85       | 1,25       |
|                                                   | 100 psi  | cfm    | 42           |              | 30         | 44         |
|                                                   | 10 barov | m³/min | 1            | –            | 0,75       | 1          |
|                                                   | 145 psi  | cfm    | 35           |              | 27         | 35         |
|                                                   | 13 barov | m³/min | 0,85         | –            | 0,65       | 0,85       |
|                                                   | 190 psi  | cfm    | 30           |              | 22         | 30         |
|                                                   | 15 bar   | m³/min | –            | 1            | 0,55       | 0,75       |
|                                                   | 215 spi  | cfm    |              | 35           | 19         | 27         |
| Tip motorja                                       |          |        | Honda GX 630 | Honda GX 630 | Innomotics | Innomotics |
| Nazivna moč motorja (kW)                          |          |        | 15,5         | 15,5         | 5,5        | 7,5        |
| Priprava stisnjenega zraka                        |          |        | Opcija       | Opcija       | Opcija     | Opcija     |



Kompaktne naprave

|                                                   |          |        | e-power     |              |               |            |            |            |
|---------------------------------------------------|----------|--------|-------------|--------------|---------------|------------|------------|------------|
| Model                                             |          |        | M 20        | M 27         | M 30          | M 27E      | M 31E      | M 50E      |
| Prostorninski tok pri najv. obratovalnem nadtlaku | 7 barov  | m³/min | 2           | 2,6          | 2,9           | 2,6        | 3,15       | 5          |
|                                                   | 100 psi  | cfm    | 71          | 92           | 100           | 92         | 110        | 180        |
|                                                   | 10 barov | m³/min | –           | 2,1          | –             | –          | 2,6        | 3,8        |
|                                                   | 145 psi  | cfm    |             | 74           |               |            | 92         | 135        |
|                                                   | 12 barov | m³/min | –           | 1,9          | –             | –          | 2,3        | –          |
|                                                   | 175 psi  | cfm    |             | 67           |               |            | 81         |            |
|                                                   | 14 bar   | m³/min | –           | 1,6          | –             | –          | 1,9        | –          |
|                                                   | 200 spi  | cfm    |             | 57           |               |            | 67         |            |
| Tip motorja                                       |          |        | Kubota D722 | Kubota D1105 | Kubota D1105T | Innomotics | Innomotics | Innomotics |
| Nazivna moč motorja (kW)                          |          |        | 14,7        | 18,2         | 18,2          | 15         | 22         | 25         |
| Priprava stisnjenega zraka                        |          |        | Opcija      | Opcija       | Opcija        | Opcija     | Opcija     | Opcija     |
| Generator (kVA)                                   |          |        | –           | 6,5          | –             | –          | –          | –          |




Multitalenti

| Model                                         |          |        | M 44             | M 58 utility   | M 59          | M 65             |
|-----------------------------------------------|----------|--------|------------------|----------------|---------------|------------------|
| Prostorninski-tok pri najv. obratov. nadtlaku | 7 barov  | m³/min | 4,1              | 5,1            | –             | –                |
|                                               | 100 psi  | cfm    | 145              | 180            |               |                  |
|                                               | 10 barov | m³/min | –                | 4,35           | 4,7 pV 5,5    | 5,8 pV 6,6       |
|                                               | 145 psi  | cfm    |                  | 155            | 165 195       | 195 230          |
|                                               | 14 bar   | m³/min | –                | –              | 3,8 pV 4,7    | 4,6 pV 5,8       |
|                                               | 200 spi  | cfm    |                  |                | 135 165       | 165 195          |
| Tip motorja                                   |          |        | Kubota V1505CR-T | Kubota V2403CR | Hatz 3H50TICD | Kubota V2403CR-T |
| Nazivna moč motorja (kW)                      |          |        | 27,5             | 35,5           | 43,5          | 47,9             |
| Priprava stisnjenega zraka                    |          |        | Opcija           | Opcija         | Opcija        | Opcija           |
| Generator (kVA)                               |          |        | 8,5/13           | –              | 8,5/13        | –                |



Paketi moči

| Model                                          |          |        | M 76             |    | M 81          |     | M 125             |     | M 171             |    |      |
|------------------------------------------------|----------|--------|------------------|----|---------------|-----|-------------------|-----|-------------------|----|------|
| Prostornin-skitok pri najv. obratov. nadtlatku | 7 barov  | m³/min | -                |    | -             |     | -                 |     | 17                |    |      |
|                                                | 100 psi  | cfm    |                  |    |               |     |                   |     | 600               |    |      |
|                                                | 10 barov | m³/min | 6,8              | pV | 7,7           | 7,1 | pV                | 8,3 | -                 |    |      |
|                                                | 145 psi  | cfm    | 240              |    | 270           | 250 |                   | 295 |                   |    |      |
|                                                | 14 bar   | m³/min | 5,3              | pV | 6,1           | 5,3 | pV                | 6,4 | 11,5              | pV | 11,5 |
|                                                | 200 spi  | cfm    | 190              |    | 215           | 190 |                   | 230 | 405               |    | 550  |
| Tip motorja                                    |          |        | Kubota V3307CR-T |    | Hatz 4H50TICD |     | Deutz TCD 4.1 L04 |     | Deutz TCD 6.1 L06 |    |      |
| Nazivna moč motorja (kW)                       |          |        | 55,4             |    | 55,4          |     | 105               |     | 129               |    |      |
| Priprava stisnjenega zraka                     |          |        | Opcija           |    | Opcija        |     | Opcija            |     | Opcija            |    |      |
| Generator (kVA)                                |          |        | -                |    | 8,5/13        |     | 13                |     | -                 |    |      |



Veliki kompresorji

Veliki kompresorji

|                                                    |            |        |              |    | e-power    |            |      |
|----------------------------------------------------|------------|--------|--------------|----|------------|------------|------|
| Model                                              |            |        | M 255        |    | M 250E     | M 255E     |      |
| Prostorninski tok pri najv. obratovalnem nadtlatku | 8,6 barov  | m³/min | –            |    | 25         | –          |      |
|                                                    | 125 psi    | cfm    |              |    | 885        |            |      |
|                                                    | 10,3 barov | m³/min | 24,8         | pV | 26,5       | 20,4       | 24,7 |
|                                                    | 150 psi    | cfm    | 875          |    | 950        | 720        | 875  |
|                                                    | 12 barov   | m³/min | –            |    | –          | 19,9       |      |
|                                                    | 175 psi    | cfm    |              |    |            | 705        |      |
|                                                    | 14 bar     | m³/min | 19,7         | pV | 25,5       | 16,2       | –    |
|                                                    | 200 spi    | cfm    | 695          |    | 900        | 570        |      |
| Tip motorja                                        |            |        | Cummins B6.7 |    | Innomotics | Innomotics |      |
| Nazivna moč motorja (kW)                           |            |        | 210          |    | 132        | 160        |      |
| Priprava stisnjenega zraka                         |            |        | Opcija       |    | Opcija     | Opcija     |      |

