

KAESER
KOMPRESSORER®



MOBILAIR-program med CE-overensstemmelse

Mobile kompressorer med SIGMA PROFIL , der er anerkendt over hele verden
Kapacitet fra 1,2 til 48,1 m³/min.

www.kaeser.com

Alternative drev

			e-power			
Model			M 13	M 17	M 10E	M 13E
Volumenstrøm ved maks. driftsovertryk	7 bar	m³/min.	1,2	–	0,85	1,25
	100 psi	cfm	42		30	44
	10 bar	m³/min.	1	–	0,75	1
	145 psi	cfm	35		27	35
	13 bar	m³/min.	0,85	–	0,65	0,85
	190 psi	cfm	30		22	30
	15 bar	m³/min.	–	1	0,55	0,75
	215 psi	cfm		35	19	27
Motortype			Honda GX 630	Honda GX 630	Innomotics	Innomotics
Motormærkeeffekt (kW)			15,5	15,5	5,5	7,5
Trykluftbehandling			Ekstraudstyr	Ekstraudstyr	Ekstraudstyr	Ekstraudstyr



Kompakte enheder

			e-power					
Model			M 20	M 27	M 30	M 27E	M 31E	M 50E
Volumenstrøm ved maks. driftsovertryk	7 bar	m³/min.	2-	2,6	2,9	2,6	3,15	5
	100 psi	cfm	71	92	100	92	110	180
	10 bar	m³/min.	–	2,1	–	–	2,6	3,8
	145 psi	cfm		74			92	135
	12 bar	m³/min.	–	1,9	–	–	2,3	–
	175 psi	cfm		67			81	
	14 bar	m³/min.	–	1,6	–	–	1,9	–
	200 psi	cfm		57			67	
Motortype			Kubota D722	Kubota D1105	Kubota D1105T	Innomotics	Innomotics	Innomotics
Motormærkeeffekt (kW)			14,7	18,2	18,2	15	22	25
Trykluftbehandling			Ekstraudstyr	Ekstraudstyr	Ekstraudstyr	Ekstraudstyr	Ekstraudstyr	Ekstraudstyr
Generator (kVA)			–	6,5	–	–	–	–




Multitalenter

Model			M 44	M58 utility	M 59	M 65
Volumenstrøm ved maks. driftsovertryk	7 bar	m³/min.	4,1	5,1	–	–
	100 psi	cfm	145	180		
	10 bar	m³/min.	–	4,35	4,7 pV 5,5	5,8 pV 6,6
	145 psi	cfm		155	165 195	195 230
	14 bar	m³/min.	–	–	3,8 pV 4,7	4,6 pV 5,8
	200 psi	cfm			135 165	165 195
Motortype			Kubota V1505CR-T	Kubota V2403CR	Hatz 3H50TICD	Kubota V2403CR-T
Motormærkeeffekt (kW)			27,5	35,5	43,5	47,9
Trykluftbehandling			Ekstraudstyr	Ekstraudstyr	Ekstraudstyr	Ekstraudstyr
Generator (kVA)			8,5 / 13	–	8,5 / 13	–



Kraftfulde versioner

Model			M 76		M 81		M 125		M 171	
Volumenstrøm ved maks. driftsovertryk	7 bar	m³/min.	-		-		-		17	
	100 psi	cfm							600	
	10 bar	m³/min.	6.8	pV	7.7	7.1	pV	8.3	-	
	145 psi	cfm	240		270	250		295		
	14 bar	m³/min.	5.3	pV	6.1	5.3	pV	6.4	11,5	
	200 psi	cfm	190		215	190		230		
Motortype			Kubota V3307CR-T		Hatz 4H50TICD		Deutz TCD 4.1 L04		Deutz TCD 6.1 L06	
Motormærkeeffekt (kW)			55,4		55,4		105		129	
Trykluftbehandling			Ekstraudstyr		Ekstraudstyr		Ekstraudstyr		Ekstraudstyr	
Generator (kVA)			-		8,5 / 13		13		-	



Store kompressorer

Model			M 255		e-power	
					M 250E	M 255E
Volumenstrøm ved maks. driftsovertryk	8,6 bar	m³/min.	-		25	-
	125 psi	cfm			885	
	10,3 bar	m³/min.	24,8	pV	26,5	24,7
	150 psi	cfm	875		950	875
	12 bar	m³/min.	-		-	19,9
	175 psi	cfm				705
	14 bar	m³/min.	19,7	pV	25,5	-
	200 psi	cfm	695		900	
Motortype			Cummins B6.7		Innomotics	Innomotics
Motormærkeeffekt (kW)			210		132	160
Trykluftbehandling			Ekstraudstyr		Ekstraudstyr	Ekstraudstyr

